
















06/2018

Mod: **ORIZ/2P**

Production code: **F1000001**



**Diamond**  
catering equipment

 <b>Modello - Model - Model - Gerätetyp</b>	<b>ORIZ/2P</b>	<b>ORIZ/3G</b>	<b>ORIZ/3M</b>
	Code Production	F 1 0 0 0 0 0 1	F 1 2 0 0 0 0 1
	<b>ORIZ/2P-TR</b>	<b>ORIZ/3G-TR</b>	<b>ORIZ/3M-TR</b>
	Code Production	F 1 0 0 0 0 0 2	F 1 2 0 0 0 0 2
			
 Description	<b>F100</b>	<b>F120</b>	<b>F200</b>
 Range	+4°C +8°C	+4°C +8°C	+4°C +8°C
Operating Mode	Ventilated	Ventilated	Ventilated
 Gross Capacity [l.]	100	150	190
 External Dimension	Width		
	800	800	1000
	Depth		
410	410	410	
Height			
700	915	915	
 Internal Dimension	Width		
	745	745	945
	Depth		
310	310	310	
Height			
360	580	580	
 Defrost	Type of defrost		
	Stop Compressor	Stop Compressor	Stop Compressor
	N° Defrost in 24 hrs.		
	3	3	3
Evaporation of defrost water			
Automatic by hot gas	Automatic by hot gas	Automatic by hot gas	
 Compressor 	T° Evaporation [°C]		
	-10	-10	-10
	Model		
	NB6152GK	NB6152GK	NB6152GK
	Power HP		
1/4	1/4	1/4	
Refrigerant Power [watt]			
415	415	415	
 Refrigerant	Type		
	R404a	R404a	R404a
Refrigerant quantity [gr]			
180	180	180	
 Total Power [ Watt - A max]	380 - 2,2		
	Supply Voltage		
230V /50Hz 1+N	230V /50Hz 1+N	230V /50Hz 1+N	
Net weight [kg]			
70	85	95	

● = Yes   □ = Optional