

02/2016

Mod: RPAV15



Production code: 8035028



Diamond
catering equipment

	ELEMENTO CON VASCA O PIANO REFRIGERATO- UNITS WITH BASIN OR REFRIGERATED SHELF-ELEMENTE MIT BEHÄLTER ODER GEKÜHLTER ABLAGE - ELEMENTS AVEC BAC OU PLAN REFRIGERE						VETRINA REFRIGERATA SU VASCA O PIANO - REFRIGERATED SHOWCASE UNITS ON BASIN OR SHELF - GEKÜHLTE VITRINENELEMENTEAUF BEHÄLTER ODER ABLAGE- VITRINE REFRIGEREESUR BAC OU PLAN			
DATI TECNICI- TECHNICAL DATA	RCT 12 (EGVR12)	RCT 15 (EGVR15)	RCA 15 (EVVR15)	RPT 12 (EGPR12)	RPT 15 (EGPR15)	RPA 15 (EVPR15)	RCTV 15 (VTRVG15)	RCAV 15 (VTRVVR15)	RPTV 15 (VTRPG15)	RPAV 15 (VTRPVR15)
Vano- Compartment type- Fach	OPEN A JOUR	OPEN A JOUR	REFRIGERATED REFRIGERE	OPEN A JOUR	OPEN A JOUR	REFRIGERATED REFRIGERE	OPEN A JOUR	REFRIGERATED REFRIGERE	OPEN A JOUR	REFRIGERATED REFRIGERE
	CON VASCA REFRIGERATA - WITH BASIN - MIT GEKÜHLTEM BEHÄLTER - AVEC BAC			CON PIANO REFRIGERATO - WITH SHELF MIT GEKÜHLTER ABLAGE - AVEC PLAN			CON VASCA REF. - WITH BASIN MIT GEKÜHLTEM BEHÄLTER - AVEC BAC		CON PIANO REF. - WITH SHELF MIT GEKÜHLTER ABLAGE - AVEC PLAN	
Dimensioni esterne- Overall dimensions										
L=lunghezza- length- Länge- longueur :mm	1200	1500	1500	1200	1500	1500	1500	1500	1500	1500
P=profondità-depth- Tiefe- profondeur: mm	700	700	700	700	700	700	700	700	700	700
H = altezza- height- Höhe- hauteur: mm	900	900	900	900	900	900	1620	1620	1620	1620
P. con scorrevassoI- with tray slide mm.	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000
Dim. vetrina Showcase dimensions : mm										
Lunghezza - length - Länge - longueur							1491	1491	1491	1491
Profondità – depth - Tiefe- profondeur							673	673	673	673
Altezza – height – Höhe - hauteur							700	700	700	700
Dim. vano- Compartment dimensions: mm										
Lunghezza - length - Länge - longueur	600	900	800	600	900	800	900	800	900	800
Profondità – depth - Tiefe- profondeur	590	590	540	590	590	540	590	540	590	540
Altezza – height – Höhe - hauteur	420	420	350	420	420	350	420	350	420	350
Capacità vano neutro-Neutral compartment capacity- Kapazität neutrales Fach litri/litres	148	223	/	148	223	/	223	/	223	/
Capacità cella refrigerata - Cooler capacity- Kapazität Kühlzelle litri-litres	/	/	151	/	/	151	/	151	/	151
Tipo di porte- Door type- Typ der Türen- Type de portes	/	/	Battenti - Hinged Flügeltüren - Battant	/	/	Battenti - Hinged Flügeltüren - Battant	/	Battenti - Hinged Flügeltüren - Battant	/	Battenti - Hinged Flügeltüren - Battant
N. di porte- N° of doors- Anzahl der Türen	/	/	2	/	/	2	/	2	/	2
Dimensioni A=vasca/basin B=piano/shelf										
Lunghezza - length - Länge – longueur :mm	960	1280	1280	960	1280	1280	1280	1280	1280	1280
Profondità – depth - Tiefe- profondeur :mm	510	510	510	510	510	510	510	510	510	510
Altezza – height – Höhe – hauteur : mm	210	210	210	20	20	20	210	210	20	20
Capacità vasche- Basin capacity- Kapazität	3 GN 1/1	4 GN 1/1	4 GN 1/1				4 GN 1/1	4 GN 1/1	4 GN 1/1	4 GN 1/1
Temp.vasca/piano- Basin/shelf temperature - Temperatur Behälter/Ablage °C	+ 4 / + 10 °C	+ 4 / + 10 °C	+ 4 / + 10 °C	- 10 / - 3 °C	- 10 / - 3 °C	- 10 / - 3 °C	+ 4 / + 10 °C	+ 4 / + 10 °C	- 10 / - 3 °C	- 10 / - 3 °C
Temp. Cella-Temp.cooler- Temp.der Zelle	/	/	+2 / +10 °C	/	/	+2 / +10 °C	/	+2 / +10 °C	/	+2 / +10 °C
Temp.Vetrina-Showcase temperature-Temperatur Vitrine-Température vitrine °C							+ 4 °C	+ 4 °C	+ 4 °C	+ 4 °C
Illuminazione vetrina-Showcase lighting- Vitrinenbeleuchtung- Eclairage vitrine							SI / YES	SI / YES	SI / YES	SI / YES
Portine clapet lato cliente- Top-hinged doors customer side- Klappen auf Kundenseite - Portes clapet côté client							3 + 3	3 + 3	3 + 3	3 + 3
Portine vetro scorrevoli lato operatore- Sliding glass doors operator side- Glasschiebetüren auf Bedienerseite- Portes vitrées coulissantes côté opérateur							2	2	2	2
Fluido refrigerante-Coolant type- Kühlmittel	R404A	R404A	R404A	R404A	R404A	R404A	R404A	R404A	R404A	R404A
Potenza totale-Total power-Gesamtleistung KW	0,5	0,5	0,5	0,5	0,5	0,5	0,6	0,6	0,6	0,6
Tensione alimentazione- Supply voltage- Speisespannung- Tension alimentation	230V - 1N	230V - 1N	230V - 1N	230V - 1N	230V - 1N	230V - 1N	230V - 1N	230V - 1N	230V - 1N	230V - 1N
Peso Max-Max weight-Höchstgewicht-Poids (Kg).	120	130	145	120	130	145	165	180	165	180

Mod. : RCAV 15 (8035026) – RPAV 15 (8035028)



A = INGANG VOEDINGSKABEL
A = ELECTRIC CABLE IN
A = KABELEINFÜHRUNG
A = ENTREE CABLE ELECTRIQUE