



**MOD : DRP12-2B**

**Production code : 30000033918**

**06/2025**

## Technical data sheet



***DRP12-2B***

### **CHARACTERISTICS**

|                   |            |                     |
|-------------------|------------|---------------------|
| Climate class     |            | : 4(CC2 to EN22044) |
| Temperature range | (°C)       | : +1 / +9°C         |
| Power             | ( W )      | : 730W / 4,3A       |
| Voltage/freq.     | ( V / Hz.) | : 220-240v / 50HZ   |

### **TECHNICAL SPECIFICATIONS**

|                       |           |                                       |
|-----------------------|-----------|---------------------------------------|
| External dimensions   | (WXDXH)mm | : 1200x760x2078                       |
| Internal dimensions   | (WXDXH)mm | : 1125x622x1571                       |
| Package dimensions    | (WXDXH)mm | : 1230x770x2139                       |
| Gross volume          | (L)       | : 1142                                |
| Net volume            | (L)       | : 1088                                |
| Gross weight          | (kg)      | : 199                                 |
| Net weight            | (kg)      | : 185                                 |
| Outer body            |           | : 0.6 mm CRS                          |
| Inner liner           |           | : 0.45 mm PRE-PAINTED                 |
| Insulation material   |           | : Rigid P.U.                          |
| Insulation density    |           | : 38~40 kg/m³                         |
| Internal light        |           | : Yes 2 x Vertical Led                |
| Canopy light          |           | : No                                  |
| Light Switch          |           | : Yes                                 |
| Door Switch           |           | : Yes                                 |
| Levelling leg (front) |           | : Yes                                 |
| Levelling leg (back)  |           | : No                                  |
| Roller                |           | : 4 Castor                            |
| Comp. capacity        |           | : CUBIGEL, 2065 W                     |
| Evaporator            |           | : FIN CU                              |
| Evap. ventilator      |           | : 2 x 5/33W Non Ec Axial Fan - SAIWEI |
| Condenser             |           | : WOT                                 |
| Cond. ventilator      |           | : 7/38W Non Ec Axial Fan - SAIWEI     |
| Thermostat            |           | : MECHANIC                            |
| Refrigerant           |           | : R290                                |
| Refrigerant charge    | ( g )     | : 122 grams                           |
| Approvals             |           | : CE,ROHS                             |

\* External depth is without back stopper.

