



**MOD : CBT151/R2**

**Production code : LF15TE**

**12/2025**

Fiche technique / Scheda tecnica / Ficha técnica / Technisches Datenblatt /  
Technical datasheet / Technisch gegevensblad



## Dati tecnici

## Technical Data

|                             |                             |                      |
|-----------------------------|-----------------------------|----------------------|
| DIMENSIONI (L x P x H)      | DIMENSIONS (L x P x H)      | 800 x 825 x 1921 mm  |
| CON IMBALLO (L x P x H)     | WITH EMBALLAGE (L x P x H)  | 820 x 850 x 2080 mm  |
| LARGHEZZA LUCE PORTA        | WIDTH DOOR LIGHT            | 670 mm               |
| ALTEZZA LUCE PORTA          | HEIGHT DOOR LIGHT           | 1150 mm              |
| PROFONDITÀ INTERNA          | INTERIOR DEPTH              | 730 mm               |
| SPESSORE                    | THICKNESS                   | 60 mm                |
| CLASSE CLIMATICA            | CLIMATE CLASS               | 15 GN 1/1            |
| CAPACITÀ ABBATTIMENTO       | BLAST CHILLING CAPACITY     | 48 Kg                |
| CAPACITÀ CONGELAMENTO       | FREEZING CAPACITY           | 32 Kg                |
| POTENZA ELETTRICA           | POWER INPUT                 | 2080 W               |
| ALLESTIMENTO CATERING       | CATERING LAYOUT             | 15 GN 1/1            |
| ALLESTIMENTO BAKING         | BAKING LAYOUT               | 15 EN 600x400        |
| PASSO TEGLIE                | PAN CLEARANCE               | 65 mm                |
| PESO NETTO                  | NET WEIGHT                  | 173                  |
| PESO LORDO                  | GROSS WEIGHT                | 205                  |
| CAVO ELETTRICO              | POWER CABLE                 | 16A EU PLUG          |
| ALIMENTAZIONE ELETTRICA     | POWER SUPPLY                | 230v - 1/50Hz        |
| TUBO SCARICO ACQUA          | DRAINAGE HOSE               | Ø ½"                 |
| CONTROLLO CICLO: A TEMPO    | CYCLE CONTROL: TIMED        | Si                   |
| CONTROLLO CICLO: A SPILLONE | CYCLE CONTROL: SENSOR PROBE | Si                   |
| CORPO ESTERNO               | EXTERIOR                    | AISI 304 finitura SB |
| INGOMBRO                    | ENCUMBRANCE                 | 1.4 m3               |

Temp. evap. -10°C, temp. cond. +45°C / Evap. temp. -10°C, cond. temp. +45°C

