



**MOD : SGBT/20S**

**Production code : 228708**

**01/2026**

**PNC(s):** 20 GN 1/1 BOILER NAT EU  
**FILE:** 41A401713 - BOILER NAT EU x 201  
 23-01-25 13:24

ID	Mnemonic	Value	Min	Default	Max	M.U.	Table
24	APPL	0	0	0	1		{0,"Combi"} {1,"Convection"}
26	bPHI	97	0	97	99	°C	
381	bISI	84	0	84	99	°C	
426	dISG	5	0	5	250		
460	AdAt	900	60	900	3600	s	
461	AdMt	50	30	50	120	°C	
462	AdEt	300	180	300	1800	s	

Description
Appliance level
Boiler preheating temperature
Boiler temperature to be kept in stop mode
Boost duration for ISG when no boiler
Boiler activation time to trigger boiler drain
Maximum boiler temperature to enable automatic drain
Automatic boiler drain emptying time

PNC(s): ALL  
FILE: 41A406106 - WATER SPRAY  
13/11/2020 16:12:46

ID	Mnemonic	Value	Min	Default	Max	M.U.	Table	Description
444	MAdM	160	20	160	300	°C		Maximum cavity temperature for water spray activation

PNC(s): ALL  
FILE: 41A406505 - BRAND DIAMOND  
31/05/2024 13:57:09

ID	Mnemonic	Value	Min	Default	Max	M.U.	Table	Description
346	BrAn	2	0	0	5		{0,"Electrolux"} {1,"Zanussi"} {2,"Diamond"} {3,"Multi Brand"}	Selects the brand of the appliance. This selection impacts on function names and availability

PNC(s): GN 1/1  
FILE: 41A406705 - FIR 450  
23/09/2020 12:10:06

ID	Mnemonic	Value	Min	Default	Max	M.U.	Table	Description
----	----------	-------	-----	---------	-----	------	-------	-------------

PNC(s): TOUCH  
FILE: 41A407305 - FSC  
23/09/2020 13:47:47

ID	Mnemonic	Value	Min	Default	Max	M.U.	Table	Description
22	FFSC	1	0	1	1		{0,"Disabled"} {1,"Enabled"}	Food Safe Control factory setting
100	FFdP	0	0	0	1		{0,"Disabled"} {1,"Enabled"}	F driven phase feature factory setting
130	FFSC	0	0	0	1		{0,"Disabled"} {1,"Enabled"}	Force FSC risk setting on start
131	diSF	0	0	0	1		{0,"Disabled"} {1,"Enabled"}	Display F value on screensaver
132	FSrd	1	0	1	1		{0,"Standard"} {1,"High"}	FSC default risk level

PNC(s): ALL  
FILE: 41A407405 - LAMBDA  
23/09/2020 13:51:06

ID	Mnemonic	Value	Min	Default	Max	M.U.	Table	Description
6	LAMB	1	0	1	1		{0,"Disabled"} {1,"Enabled"}	Lambda Probe

PNC(s): ALL  
FILE: 41A407605 - PROBE MULTI POINT  
23/09/2020 13:56:24

ID	Mnemonic	Value	Min	Default	Max	M.U.	Table	Description
90	Pfb	2	0	2	2		{0,"None"} {1,"1-Point"} {2,"6-Point"}	Food core temperature probe type

PNC(s): TOUCH  
FILE: 41A407805 - FULL AUTOIMATIC  
11-09-25 13:14

ID	Mnemonic	Value	Min	Default	Max	M.U.	Table
15	Faut	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
151	AFSb	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
313	ASSF	4	1	4	4		{1,"Fan speed 1"} {2,"Fan speed 2"} {3,"Fan speed 3"} {4,"Fan speed 4"}

Description
Automatic mode factory setting
Automatic: show recipe graph form factory setting
Sous vide fan speed

PNC(s): ALL  
FILE: 41A408710 - LED VERTICAL 3VETRI  
28/06/2021 16:27:59

ID	Mnemonic	Value	Min	Default	Max	M.U.	Table	Description
455	LMPM	6	0	0	6		{0,"OFF"} {1,"T12Vdx"} {2,"T12Vsx"} {3,"T13Vdx"} {4,"T13Vsx"} {5,"V2V"} {6,"V3V"}	Lamp mode

PNC(s): 20 GN 1/1 GAS  
 FILE: 411413513 - PARAM BASE 201 GAS T  
 18-06-25 08:43

ID	Mnemonic	Value	Min	Default	Max	M.U.	Table
1	GAS	1	0	0	1		{0,"Electric"} {1,"Gas"}
3	FAhr	0	0	0	1		{0,"C"} {1,"F"}
5	rod	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
6	LAMb	0	0	1	1		{0,"Disabled"} {1,"Enabled"}
7	FCLn	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
10	dEMo	0	0	0	2		{0,"Disabled"} {1,"Event mode"} {2,"Portable"}
12	Phbo	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
13	FMAh	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
14	PrEh	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
15	Faut	0	0	1	1		{0,"Disabled"} {1,"Enabled"}
22	FFSC	0	0	1	1		{0,"Disabled"} {1,"Enabled"}
24	APPL	0	0	0	1		{0,"Combi"} {1,"Convection"}
25	APPM	4	0	0	5		{0,"LW 6 1/1"} {1,"LW 6 2/1"} {2,"LW 10 1/1"} {3,"LW 10 2/1"} {4,"LW 20 1/1"} {5,"LW 20 2/1"}
26	bPHt	0	0	97	99	°C	
31	tHMA	220	180	220	300	°C	
32	trMA	180	150	180	300	°C	
33	trMn	30	0	30	180	°C	
38	ArEC	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
39	grEn	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
40	FgrA	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
42	FgSd	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
44	CLnd	2	0	2	4		{0,"Extra Strong"} {1,"Strong"} {2,"Medium"} {3,"Soft"} {4,"Rinse"}

ID	Mnemonic	Value	Min	Default	Max	M.U.	Table
45	CLnC	0	0	3	3		{0,"Solid"} {1,"Enzymatic"} {2,"Liquid"} {3,"Powder"}
46	FCLE	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
55	FCLS	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
57	FgEt	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
62	MPH	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
63	SSM	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
71	SiCd	100	25	100	130	°C	
72	SdUd	1800	1	1800	86400	s	
73	SiPd	25	15	25	120	°C	
74	SFd	4	1	4	4		{1,"Fan speed 1"} {2,"Fan speed 2"} {3,"Fan speed 3"} {4,"Fan speed 4"}
75	CHd	50	1	50	100	%	
76	CI Cd	160	25	160	300	°C	
77	CdUd	1800	1	1800	86400	s	
78	CI Pd	25	15	25	290	°C	
79	CFd	5	1	5	7		{1,"Fan speed 1"} {2,"Fan speed 2"} {3,"Fan speed 3"} {4,"Fan speed 4"} {5,"Fan speed 5"} {6,"Fan speed 6"} {7,"Fan speed 7"}
80	HHd	100	0	100	100	%	
81	HI Cd	160	25	160	300	°C	
82	HdUd	1800	1	1800	86400	s	
83	HI Pd	25	15	25	290	°C	
84	HFd	5	1	5	7		{1,"Fan speed 1"} {2,"Fan speed 2"} {3,"Fan speed 3"} {4,"Fan speed 4"} {5,"Fan speed 5"} {6,"Fan speed 6"} {7,"Fan speed 7"}
85	HI Hd	20	1	20	1800	s	
86	FECd	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
88	PdIC	5	0	5	10	°C	
89	Edt	25	PAR_PRB_CAV_DTMIN	25	120	°C	
90	Prb	0	0	2	2		{0,"None"} {1,"1-Point"} {2,"6-Point"}
100	FFdP	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
108	HCI C	70	25	70	280	°C	
109	HStC	70	25	70	100	°C	
110	HdtP	5	0	5	100	°C	
111	Pdud	1800	1	1800	86400	s	

ID	Mnemonic	Value	Min	Default	Max	M.U.	Table
114	IbAr	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
115	FFuM	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
117	FuMd	1	1	3	5		
118	FArM	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
120	ArtId	40	40	40	80	°C	
130	FSCF	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
131	dISF	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
132	FSrd	0	0	1	1		{0,"Standard"} {1,"High"}
138	CCyd	2	0	2	2		{0,"Steam"} {1,"Combr"} {2,"Hot air"}
139	HPrd	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
140	HHPd	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
141	Hfud	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
142	CPrd	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
143	SPrd	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
144	SHPd	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
145	CHPd	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
149	FSCn	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
151	AFSb	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
168	FASo	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
169	FASt	55	35	55	60	°C	
201	FAPr	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
203	FSkE	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
214	GrE	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
215	FHoE	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
216	HoE	1	0	1	1		{0,"Disabled"} {1,"Enabled"}

ID	Mnemonic	Value	Min	Default	Max	M.U.	Table
222	qSSS	80	0	80	300	°C	
225	qSSP	715	20	600	1000	s	
228	FSdE	0	0	1	1		{0,"Disabled"} {1,"Enabled"}
232	hFLS	4	1	4	7		
237	dILL	100	0	100	100		
238	Stby	0	0	1800	3599	s	
275	tSE	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
276	CSE	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
277	bSE	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
301	EOLt	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
313	ASSF	1	1	4	4		{1,"Fan speed 1"} {2,"Fan speed 2"} {3,"Fan speed 3"} {4,"Fan speed 4"}
314	AMAn	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
329	LAIP	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
346	BrAn	0	0	0	5		{0,"Electrolux"} {1,"Zanussi"} {2,"Diamond"} {3,"Multi Brand"}
348	rtCE	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
349	hPOE	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
381	btSt	0	0	84	99	°C	
408	tPrn	60	60	60	3600	s	
410	PdtE	20	0	20	100	°C	
415	dtCP	5	0	5	50	°C	
416	FCLP	0	0	1	1		{0,"Disabled"} {1,"Enabled"}
417	StF	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
418	rECt	40	0	20	600	s	
419	CdEt	60	0	60	600	s	
422	EdM	0	0	0	1		{0,"Disabled"} {1,"Enabled"}
423	SHMF	1	0	1	1		{0,"Disabled"} {1,"Enabled"}
426	dISG	0	0	5	250		

ID	Mnemonic	Value	Min	Default	Max	M.U.	Table
429	Coun	0	0	0	52		(0,"No Selection") (1,"Africa") (2,"Albania") (3,"Australia") (4,"Austria") (5,"Belarus") (6,"Belgium") (7,"Bosnia Herzegovina") (8,"Brazil") (9,"Bulgaria") (10,"Canada") (11,"Chile") (12,"China") (13,"Croatia") (14,"Cyprus") (15,"Czech Republic") (16,"Denmark") (17,"Estonia") (18,"Finnish") (19,"France") (20,"Germany") (21,"Greece") (22,"Hungary") (23,"Iceland") (24,"India") (25,"Ireland") (26,"Italy") (27,"Japan") (28,"Latin America") (29,"Latvia") (30,"Lithuania") (31,"Luxembourg") (32,"Macedonia") (0,"Disabled") (1,"Enabled")
439	FSIP	1	0	1	1		(0,"Disabled") (1,"Enabled")
442	SCIE	45	0	45	200	°C	
443	SLo	0	0	0	3599	s	
444	MAdM	20	20	160	300	°C	
454	qStE	2	0	1	2		(0,"Model") (1,"Thermocouple") (2,"Estimation")
456	LSEn	0	0	0	2		(0,"Normal") (1,"Advanced") (2,"Hidden")
458	Sdry	1	0	1	1		(0,"Disabled") (1,"Enabled")
459	2ICH	0	0	0	1		(0,"Disabled") (1,"Enabled")
460	AdAt	60	60	900	3600	s	
461	AdMt	30	30	50	120	°C	
462	AdEt	180	180	300	1800	s	
510	HICIn	0	0	0	1		(0,"Disabled") (1,"Enabled")
511	CCIn	0	0	0	1		(0,"Disabled") (1,"Enabled")
512	SCIn	0	0	0	1		(0,"Disabled") (1,"Enabled")
515	tFPd	210	60	120	6000	s	
516	bFPd	210	60	120	6000	s	
544	otA	1	0	1	1		(0,"Disabled") (1,"Enabled")

Description
Appliance type
Temperature Scale
Cooking with open door
Lambda Probe
Cleaning environment factory setting
Demo Mode
Preheat the boiler in stop mode
Manual mode factory setting
Cavity preheating
Automatic mode factory setting
Food Safe Control factory setting
Appliance level
Appliance model
Boiler preheating temperature
Maximum temperature for manual water injection
Maximum temperature to use water in cool down
Minimum temperature to use water in cool down
Advanced recovery mode
Green Options factory settings
Green Options skip rinse aid factory settings
Green Options skip drying factory settings
Default cleaning cycle

Description
Cleaning cycle chemicals
Cleaning enzymatic detergent factory settings
Cleaning solid factory settings
Green Options extend time factory settings
Manual multiphase environment
Show set and current values
Steam cycle cavity default temperature set
Steam cycle default duration
Steam cycle default core probe temperature set
Steam cycle fan speed default
Combi cycle cavity humidity set default
Combi cycle cavity default temperature set
Combi cycle default duration
Combi cycle default core probe temperature set
Combi cycle fan speed default
Hot air cycle cavity humidity set default
Hot air cycle cavity default temperature set
Hot air cycle default duration
Hot air cycle default core probe temperature set
Hot air cycle fan speed default
Hot air cycle cavity initial humidification set default
Delta T cooking factory setting
Minimum difference between cavity and probe set temperatures
DeltaT cooking default difference
Food core temperature probe type
F driven phase feature factory setting
Convection holding phase default temperature
Steam holding phase default temperature
Probe cooking holding phase default temperature
Pause cycle default duration

Description
Bottom drawer info bar
Smoker feature factory setting
Smoker default level
Aroma feature factory setting
Aroma feature default temperature
Force FSC risk setting on start
Display F value on screensaver
FSC default risk level
Preferred cooking cycle
Hot air cycle default probe driven
Hot air cycle half power feature
Hot air cycle smoker feature
Combi cycle default probe driven
Steam cycle default probe driven
Steam cycle half power feature
Combi cycle half power feature
Show consumption estimation factory setting
Automatic show recipe graph form factory setting
Automatic switching off factory setting
Automatic switching off temperature threshold factory setting
Programs ambient factory setting
Skyhub ambient factory setting
Graphics ambient user setting
Hood ambient factory setting
Hood ambient user setting

Description
Threshold temperature for quenching system driven by hydraulic drain sensor
Period for the quenching system control for hydraulic safety control
Enable Skyduo factory setting
Maximum fan speed level in steam
Sets display backlight luminosity level
Sets the inactivity time after which the machine enters in standby mode. Set 0 to disable standby
Training secondary menu enabled
Chiller secondary menu enabled
Base secondary menu enabled
Enables the End of Line Testing functionality
Sous vide fan speed
Manual mode user setting
Launch Wizard at startup
Selects the brand of the appliance. This selection impacts on function names and availability
Enables the RTC
Enables the possibility to set the half power functionality
Boiler temperature to be kept in stop mode
User HACCP data log sample time
Delta temperature to stop the preheating in advance for temperature lower than 100C
Cleaning precool setpoint delta
Cleaning powder factory settings
Show display touch feedback on screen
Minimum recovery temperature and humidity time
Cooldown extension timeout
Enable the water spray component user setting
Skyhub configuration management add and delete factory setting
Boost duration for ISG when no boiler

Description
Selects the country
Enables the possibility to create messages to be displayed during programs execution factory setting
Setpoint for components compartment temperature
Sets the inactivity time, expressed in seconds, after which the door LED lamps are turned off. Set 0 to disable this function.
Maximum cavity temperature for water spray activation
Quenching system managing method
Lambda error management
Forced drying on switch off
2 touches mode
Boiler activation time to trigger boiler drain
Maximum boiler temperature to enable automatic drain
Automatic boiler drain emptying time
Convection Cycle Continuous default
Combi Cycle Continuous default
Steam Cycle Continuous default
Top fan half period seconds
Bottom fan half period seconds
Enables machine updates from remote OTA