

MOD : BSC/300-20

Production code : GFK 300

BSC - Fiche technique



Modèle #	BSC /150-10	BSC/ 300-20
Capacité Maximale	150kg	300kg
Précision	10g	20g
Répétabilité (Std Dev)	20g	40g
Linéarité \pm	20g	40g
Unités de Mesure	BSC /150-10	BSC/ 300-20
Temps de Stabilisation	2-3 Secondes	
Température de Fonctionnement	-10°C à +40°C / +14°F à +104°F	
Alimentation	12vDC 800mA	
Calibrage	Externe	
Masse de Calibrage	Sélectionnable par l'Utilisateur	
Écran	Écran vert rétroéclairé de 18 mm avec suivi de la capacité	
Construction de la Balance	Soudée en acier peint, plateau supérieur en acier inoxydable 304, boîtier d'indicateur en ABS	
Taille du Plateau	400mm x 500mm	
Poids Net	13.57kg	
Fonctionnalités	Pesage / Comptage / Pourcentage / Fonction de Maintien / RS232	

BSC - Technical data sheet



Model #	BSC /150-10	BSC/ 300-20
Maximum Capacity	150kg	300kg
Readability	10g	20g
Repeatability (Std Dev)	20g	40g
Linearity \pm	20g	40g
Units of Measure	Kilograms and grams	
Stabilization Time	2-3 Secs	
Operating Temperature	-10°C to +40°C / +14°F to +104°F	
Power Supply	12vDC 800mA	
Calibration	External	
Calibration Mass	User Selectable	
Display	Backlit Green display 18mm with capacity tracker	
Scale Housing	Welded steel painted base, stainless steel grade 304 Top pan, ABS indicator housing	
Pan Size	400mm x 500mm	
Net Weight	13.57kg	
Features	Weighing/Counting/ Percentage/Hold function/RS232	