

08/2018

Mod: G9/BRI8

Production code: BBGBRVI98



Diamond
catering equipment

GBRVI98



S/S BOWL, GAS MONOBLOC

SEE MORE TECHNICAL DATA:

External dimensions - WxDxH (cm)	80x90x85
Tank capacity (lt-GN)	80
Total power (kW)	20,02

HIDE THE OTHER TECHNICAL DATA:

Tank dimensions - WxDxH (cm)	790x690x200
Supply (N)	230V 1N 50Hz
Weight (kg)	164
Volume (m3)	1,1

The structure is AISI 304 stainless steel 18/10 with scotch-brite finishing. The tank has AISI 304 18/10 stainless steel walls and bottom is in compound of 12 mm thickness, (mod VI) or stainless steel for more efficient heat distribution. The rounded corners and the shaped front part facilitate unloading and cleaning operations. The stainless steel lid is balanced and has strong stainless steel AISI 304 hinges and an ergonomic front handle. Water load tap placed on the front of the unit. Gas versions: stainless steel burner with multiple arms for more even heat diffusion; gas valve with thermocouple, thermostatic temperature control (75-300 °C). Electric versions: armoured heating elements in stainless steel on the external bottom of the tank; thermostatic control (75-300 °C).

