



MOD : DC502/6-PSD5

Production code : 919868

08/2026


Overall Dimension (Width-Depth-Height) *open mm 575x605(1005*)x820

Packaging Dimension (WxDxH) mm 690x670x980

Gross weight Kg 60

Net weight Kg 54

Volume mc 0,45



Interface

□	Rack size	mm	500x500
	Max door /hood opening	mm	365
	Max glasses/plate Height	mm	325/365
	General construction		single skin
	Door/hood Construction		double skin
↘	Tank construction		welded
	Tank volume	liter	20
	Tank heating element	W	2.100
	Tank surface strainers		Yes - composite
⚙️	Wash pump type		double flow
	Wash pump power	W	500
	Wash temperature	°C	60
↘	Boiler type		pressurized
	Boiler volume	liter	6
	Back-flow system		valve
	Boiler heating element	W	4.900
⚙️	Rinse booster pump		NO
	Rinse booster pump power	W	-
	Rinse temperature	°C	85
	Rinse water consumption	Liter /rack	2,4
	Optimal external water pressure	bar	2
🚰	Drain system		overflow
	Drain pump		standard built in
▶	Rinse aid dispenser		YES
	Detergent dispenser		YES
⚙️	Wash cycle	sec	60 - 120
	Electric Power	W	5.400
⚡	Electric Connection	V - ph - Hz	400V 3N 50Hz
	Fuse	A	16
	Water softner		NO
▶	Plates racks		YES
	Flat Rack		YES
	Cutterly Rack		YES
	Electric cable		YES
	Drain hose		YES
	Fill hose		YES

